## Pro-Mesh Profiled Mesh Fencing System

10

6

NAYLOR


FENCING


Pro-Mesh is a cost effective perimeter solution, offering a versatile and durable fencing system that has an attractive appearance. Pro-Mesh is easy to install using a 3008mm wide panel manufactured from 5mm wire galvanised and powder coated green and in 1.8m, 2.0m and 2.4m heights. The posts are 60x60mm box section posts again galvanised and powder coated green, pre-drilled factory fitted threaded 8mm inserts to allow for the fixing bracket and 8mm anti-tamper screw.

 Pro-Mesh panel, horizontal v shaped profile, designed to increase rigidity.
Pro-Mesh post, 60x60mm galvanised and powder coated steel post. Predrilled 8mm fixing points.


3 Pro-Mesh anti-tamper 8mm screw, steel fixing bracket and plastic post cap.


Panel	Post	Post	Wire D.	Mesh	No. of	Fixing
Height	Section	Centres	(H/V)*	Pattern	V Bars	Method
1.730m	60x60mm	3.015m	5/5mm	50x200mm	3	5 Clips
1.930m	60x60mm	3.015m	5/5mm	50x200mm	3	5 Clips
2.330m	60x60mm	3.015m	5/5mm	50x200mm	3	6 Clips








DETAIL ASSEMBLY











3008 PANEL WIDTH

## Technical

Panels wires are galvanised to EN 10244-2, class D with a minimum zinc coating of 40gr/m. Posts pregalvanised to special high grade zinc (SHG) 99.995% EN 1179:2003 grade ZI, polyester coating to RAL 6005, with an average thickness 80um



NAYLOR CONCRETE PRODUCTS LIMITED NAYLOR FENCING MATERIALS ASH LANE. GARFORTH LEEDS WEST YORKSHIRE LS25 2HQ

TELEPHONE: 0113 286 2586 FACSIMILE: 0113 286 7376 EMAIL: FENCING@NAYLOR.CO.UK WEB: WWW.FENCINGMATERIALS.CO.UK