





Construction Products Regulation

Declaration of Performance

Identification Code: ER6
Certificate Number: HS/FA/EC/FS/ER6

Serial number: EC-ER6

Intended use: Concrete lintel intended for use in walls and partitions

Manufacturer: Naylor Concrete Products Ltd, Whaley Road, Barugh Green, Barnsley, South Yorkshire, S75 1HT

Assessment and verification of constancy of performance: System 3

Relevant harmonised standard: BS EN 845-2:2013+A1:2016

Lucideon Ltd (Notified Body No. 1289) carried out initial type testing to EN846-9:2016 under AVCP system 3 and issued test report Ref: UK214995/Ref. 1/CR2

Declared Performance

ER6	Lintel Length							
Essential Characteristics	900	1200	1500	1800	2100	2400	2700	3000
Load bearing capacity (kNm-1)	27.18	15.95	11.19	7.16	4.91	3.52	2.61	1.98
Deflection at 1/3 of load capacity (mm)	1.16							
Thermal resistance	Thermal conductivity λ 10,dry, mat (according to EN 1745) 1.52 W/m.K							
Resistance to fire	30 minutes							
Durability of performance characteristics against corrosion	C2 - from table C3 EN 845-2:2016 (E)							
Durability of performance characteristics against freeze/thaw cycle	Resistant							
Water absorption	1.15 C _{w.s}							
Water vapour permeability	NPD							
Dangerous substances	None							

The performance of the product identified is in conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer identified.