



EN 15258:2008

DECLARATION OF PERFORMANCE

Rockwall

Identification No. WRW

1. Product Type

Unique identification code of the product type: **Rockwall Retaining Walls**

2. Type,

batch or serial number or any other element allowing identification of the construction product as required under article 11(4): **Upto 3.8m,Anchored down/Cast in**

3. Intended Use

or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Retaining elements according to EN 15258 & BS EN1992-1-1:2004 & BS EN1997-1:2004**

4. Name, registered trade name

or registered trade mark and contact address of the manufacturer as required in Article 11(5): **Naylor Industries
Whaley Road
Barnsley
S75 1HT**

5. Contact Address:

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): **(see 4)**

6. AVCP:


System or systems of assessment and verification of constancy of performance of the construction products as seen out in CPR, Annex V: **System 2+**

7. Notified body (hEN):

In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: **EN 15258 & BS EN1992-1-1:2004 & BS EN1997-1:2004. BSi (0086) performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.**

Declaration of Performance

8. Declared Performance

 BSI - 2797
Naylor Concrete Products, Barnsley, UK, S75 1HT
26
0086 CPR 663178 EN 15258
Retaining wall elements Precast element for gravity resistant wall
Concrete: Compressive strength $f_{ck} = 50 \text{ N/mm}^2$
Reinforcing Steel: Ultimate tensile strength $f_{tk} = 540 \text{ N/mm}^2$ Tensile yield strength $f_{yk} = 500 \text{ N/mm}^2$
Mechanical resistance (design values): Bending moment capacity (of the critical section).....74kNm
Shear capacity (of the critical section).....125 kN/m
Material safety factors applied in strength calculation: For concrete..... $\gamma_c = 1.5$ For steel..... $\gamma_s = 1.15$
For geometrical data, detailing, durability, water vapour permeability and other NPDs see the Technical documentation
Technical Documentation: Position numberNI-RW-2604-3800 Rev 1

9. The Performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of Naylor Industries Ltd by:

Paul Whyte, Managing Director
Barugh Green, Barnsley
29th of April 2026

naylor
CONCRETE

For Further Information:
Naylor Concrete Products
Whaley Road
Barnsley S75 1HT

Phone: 01226320810