

Hi-Spec & Fair Faced

One of the most specified lintels in the UK. Hi-Spec lintels are designed for high performance while remaining cost effective. Available up to 3.6m in length and offer 30 minutes fire resistance only as standard. Longer lengths up to 4.8m available on request.

Standard Finish

An extruded concrete finish for use in plastered situations. Not ideal in situations where aesthetic finish is required.

Fair Faced Finish

Designed to the same spec as our Hi-Spec range, our Fair Faced lintels have a smooth, consistent colour finish. For use in exposed/painted situations. This Type C Fair Faced finish ensures all corners, arises, and faces on the lintel are perfect.

When ordering our Fair Faced Finish, simply add 'Faced' before the range code.



Load Table Units suitable for 100mm wide walls Unfactored Loads in kN/m		S4 	R6 	R9 	R12 
Fire Resistance Available (mins)		30	30	30	30
Suitable For Foundation Use		Yes	Yes	Yes	Yes
Maximum Stock Length Available		3000mm	3000mm	3600mm Longer lengths available on request - up to 4800mm	3600mm
Available Range Finish		Standard/Faced	Standard/Faced	Standard/Faced	Standard/Faced
Length	Clear Span	100x100	100x140	100x215	100x290
900mm	700mm	15.77	38.73	96.25	127.77
1200mm	1000mm	10.90	30.87	62.92	83.26
1500mm	1200mm	9.41	27.22	50.00	77.43
1800mm	1500mm	7.21	19.32	37.15	63.07
2100mm	1800mm	5.04	13.59	28.63	47.94
2400mm	2100mm	3.70	10.04	22.61	36.95
2700mm	2400mm	2.81	7.70	18.13	28.62
3000mm	2700mm	2.19	6.06	14.48	22.77
3300mm	3000mm	n/a	4.88	11.68	18.51
3600mm	3200mm	n/a	4.27	9.78	15.79
Lintel Weight kg/m		23	34	52	70

*Other lengths available on request.

Hi-Spec & Fair Faced

Load Table Units suitable for 140mm wide walls Unfactored Loads in kN/m		R3 	S5 	R8 	R11 
Fire Resistance Available (mins)		30	30	30	30
Suitable For Foundation Use		Yes	Yes	Yes	Yes
Maximum Stock Length Available		2400mm	3600mm	3600mm Longer lengths available on request - up to 4800mm	3600mm
Available Range Finish		Standard/Faced	Standard/Faced	Standard/Faced	Standard/Faced
Length	Clear Span	140x100	140x140	140x215	140x290
900mm	700mm	55.12	58.05	117.41	155.63
1200mm	1000mm	32.59	36.52	71.19	101.39
1500mm	1200mm	23.01	27.35	54.50	89.79
1800mm	1500mm	14.93	19.20	41.19	68.08
2100mm	1800mm	10.42	13.67	31.18	51.69
2400mm	2100mm	7.65	10.07	23.94	39.78
2700mm	2400mm	n/a	7.68	18.46	30.76
3000mm	2700mm	n/a	6.03	14.63	24.43
3300mm	3000mm	n/a	4.83	11.84	19.82
3600mm	3200mm	n/a	4.20	10.38	16.87
Lintel Weight kg/m		34	47	72	97

*Other lengths available on request.

Hi-Spec & Fair Faced

Load Table Units suitable for 190mm wide walls Unfactored Loads in kN/m		R2 	R190 	R13 
Fire Resistance Available (mins)		30	30	30
Suitable For Foundation Use		Yes	Yes	Yes
Maximum Stock Length Available		3600mm	3600mm Longer lengths available on request - up to 4800mm	3600mm
Available Range Finish		Standard/Faced	Standard/Faced	Standard/Faced
Length	Clear Span	190x145	190x215	190x290
900mm	700mm	85.34	141.00	186.95
1200mm	1000mm	51.57	77.44	121.77
1500mm	1200mm	36.74	59.23	94.50
1800mm	1500mm	24.03	44.70	71.56
2100mm	1800mm	16.85	33.79	54.25
2400mm	2100mm	12.40	25.89	41.68
2700mm	2400mm	9.45	19.92	32.16
3000mm	2700mm	7.40	15.74	25.48
3300mm	3000mm	5.92	12.70	20.62
3600mm	3200mm	4.27	11.11	17.51
Lintel Weight kg/m		66	98	132

Load Table Units suitable for 215mm wide walls Unfactored Loads in kN/m		R7 	S8 	R14 
Fire Resistance Available (mins)		30	30	30
Suitable For Foundation Use		Yes	Yes	Yes
Maximum Stock Length Available		3600mm	3600mm Longer lengths available on request - up to 4800mm	3600mm
Available Range Finish		Standard/Faced	Standard/Faced	Standard/Faced
Length	Clear Span	215x145	215x215	215x290
900mm	700mm	100.27	152.21	202.02
1200mm	1000mm	60.61	79.20	127.15
1500mm	1200mm	42.18	60.55	96.07
1800mm	1500mm	27.71	45.67	72.71
2100mm	1800mm	19.49	34.49	55.07
2400mm	2100mm	14.38	26.40	42.27
2700mm	2400mm	10.99	20.29	32.58
3000mm	2700mm	8.62	16.01	25.78
3300mm	3000mm	6.90	12.90	20.83
3600mm	3200mm	4.98	11.27	17.67
Lintel Weight kg/m		75	111	150

*Other lengths available on request.